

PRODUCT DATA SHEET

BLACKINDUSTRY SWIR 1.7 Max



HAIP Solutions BlackIndustry SWIR 1.7 Max Spectral Imaging System is a smart line scanning (push-broom) near-infrared hyperspectral imaging camera that allows the acquisition of real-time spectral data with very high spatial resolution.

The outstanding sensitivity in the NIR range from 900 nm to 1730 nm is perfect for the use in industrial in-line applications. With a frame rate of 210 Hz at full frame and up to 1300 Hz with ROI, BlackIndustry SWIR 1.7 Max is a high performance spectral imaging system designed applications that require high light for throughput, fast data acquisition and good imaging performance.

Features

- **Smart Hyperspectral Line-Scanner**
- Designed for industrial in-line applications
- SWIR (900-1730 nm)
- Up to 420 spectral bands (selectable)
- Spatial resolution: 1280px
- Framerate: 210/1300 Hz (Full Frame/ROI)
- Internal GPU for pre-processing




BlackIndustry SWIR 1.7 Max

Hyperspectral Machine Vision Camera

Optics	
Spectral range	900-1730 nm
Spatial resolution	1280 px
Dispersion	283 nm/mm
Pixel resolution	1.4 nm/pixel
FWHM (spectral res.)	< 6 nm (15 µm slit)
Image size	5.16 (spectral) x 6.48 (spatial) mm
Smile	< 5 µm; software corrected
Keystone	< 5 µm; software corrected
Aperture	F/1.4
Slit width (default)	15 μm (10/25 μm on request)
Electronics	
Sensor type	InGaAs (SenSWIR)
Pixels in full frame	1280 (H) x 1024 (V)
Pixel size	5 x 5 μm
Radiometric resolution	10 bit
Framerate Full Frame/ROI	210/1300 Hz
Internal data processing	NVIDIA Jetson Nano, 16 GB
Connection	GigE (GenlCam compatible)
Temperature stabilization	active
Power input	24 V DC
Power consumption	< 15 W
Mechanics	
Lens mount	Standard C-Mount
Housing	Anodised aluminum
Temperature (Operation)	-10 - +50°C
Temperature (Storage)	-15 - +60°C
Size	60 * 80 * 210 mm
Weight	2 kg

BlackIndustry SWIR 1.7 is also available in a lower spatial resolution version of 640 px.

If your application requires dedicated optics, wavelength ranges or software tools, customization - our very true strength - can be done without large NRE costs.



BlackIndustry SWIR 1.7 Max - Spectral response

Ideal for food industry & recycling

The sensor is suitable for high conveyor belt speeds or chute systems, ideal for sorting applications in Food Industry or Recycling.

Data pre-processing on camera is possible, as the camera has an integrated GPU (Nvidia Jetson). All BlackIndustry series cameras are controllable via HAIP BlackStudio software, GenICam or a dedicated C++/Python API.

Combining superior optical design with advanced holographic transmission grating technology, highend electronics and a sensitive InGaAs detector, BlackIndustry SWIR 1.7 Max camera is an ideal tool for demading environments.

The hyperspectral sensor provides a spatial resolution of 1280 pixels with up to 420 spectral channels to be read in, within the wavelength range from 900 nm to 1730 nm.



